

# XMQ6127J



## Description

With a rated power of 280Kw at 2100 rpm, the Dongfeng Cummins ISL8.9E5 280B engine is used for the XMQ6127J public transit bus. 40 seats are available for passengers. The fuel tank capacity of the public transit bus is 220L. Using the ZIFF steering system and front/rear disc brake system, passengers can feel comfortable and safe.

<b>Technical Specifications</b>	
Model	XMQ6127J
<b>Dimensions</b>	
Length* Width* Height (mm)	11980*2550*3170 (With air conditioner)
Wheelbase (mm)	6000
Front overhang/rear overhang (mm)	2670/3310
Minimum ground clearance (mm)	160
<b>Capacity</b>	
Seating arrangement	40+1
Fuel tank capacity (L)	220 (L)
<b>Engine</b>	
Brand	Dongfeng CUMMINS
Model	ISL8.9E5 280B
Emission standard	Euro V
Rated power (kiwi/rpm)	280/2100
Rated torque (Name/rpm)	1060/1100-1700
Displacement (L)	8.9
<b>Transmission &amp; Clutch</b>	
Clutch	No clutch
Transmission	ZIFF 6-gear transmission with hydraulic retarded
<b>Axles</b>	
Front	Chinese
Rear	Chinese
<b>Suspension</b>	
Suspension system	Chinese 6-airbag air suspension
<b>Steering</b>	
Steering system	ZIFF
<b>Brake system</b>	
Brake system (Disc/Drum)	Front/Rear Disc
Tire	Michelin tubeless tire 275/70R22.5
ABS	WACO
<b>Body</b>	
Door & Window	
Doors	

Side Windows	Fully enclosed toughened privacy glass
Seats	
Driver	Fabric cover, King Long high back, adjustable driver seat
Passenger	Public transit bus special seat
Air Conditioner	
Type	King Long roof-mounted non-independent air conditioner
Heater	
Type	Webasto heater, heating with air blower, independent defrosting device with external recirculation
Mirror	
Type	Canada luxcerix imported rear view mirror
Other Standard Equipment	
Safety door, GPS antenna, reversing monitor, exit bell, guideboard, wheelchair telescopic footboard, double-speed driver fan, internal information display board	